

IMPREGNATED BODIES MADE OF EXPANDED GRAPHITE, PROCESS FOR  
PRODUCING SUCH BODIES AND SEALING ELEMENTS, FUEL CELL  
5 COMPONENTS AND HEAT-CONDUCTING ELEMENTS FORMED OF THE BODIES

Background of the Invention:

Field of the Invention:

10 The invention relates to a synthetic resin-impregnated body  
made of expanded or at least partially recompressed expanded  
graphite, a process for producing such a body and a sealing  
element, a fuel cell component and a heat-conducting element  
employing the body. In this context, the term "synthetic  
resin-impregnated body" is understood to mean a body made of  
15 expanded graphite which is impregnated by synthetic resin.

20 Material composites of graphite and plastics are widely used  
in many technical applications. For example, particles of  
electrographite are processed with fluoroplastics into highly  
corrosion-resistant components for the construction of  
chemical apparatus, but they are comparatively expensive due  
to the costs of the fluoroplastics and of the processing  
technique that is required. A subject which in terms of  
content is even closer to the present application is set out  
25 in U.S. Patent No. 4,265,952: expanded graphite is mixed, for  
example, with fine PTFE powder and subsequently compressed.

To that extent, the production technique differs from the impregnating technique described in the present application.

Another example of a material composite of graphite and plastics material is superficially resin-impregnated foils made of natural graphite, which are predominantly employed in the form of flat seals against particularly aggressive media. Many references to that second example are found in the technical literature.

Today, thousands of tons of foils made of natural graphite are produced worldwide every year. The process used therefor is described in European Patent Application 0 087 489 A1, U.S. Patent No. 3,404,061 and U.S. Patent No. 3,494,382. Those disclosures are incorporated by reference in the present application. The teaching of those references can be summarized as follows: an intercalating agent such as concentrated sulfuric acid, for example, acts on natural graphite, preferably platelike or flaky natural graphite, in the presence of an oxidizing agent such as concentrated nitric acid or hydrogen peroxide, for example. That results in graphite intercalation compounds that are likewise flaky or have a platelike shape. The flakes are thermally decomposed and, as a result of the gas pressure arising in their interior during that decomposition process, puff up to form loose graphite particles with a wormlike shape by brief heating, for

example by introduction into the flame of a gas burner. That product is also referred to as "expanded" graphite or as graphite expandate.

5 Expanded graphite is extremely plastic and can be readily shaped without the aid of a special binder while being compressed to a greater or lesser degree. Economically, the most important product thus produced is a flexible graphite foil, which can be produced efficiently on calender belts.

10 Such products have typical bulk densities of between 0.7 and 1.3 g/cm<sup>3</sup>. However, other parts having different geometry, for instance individual sealing bodies which, on average, are compressed to a greater degree and have bulk densities of 1.0 to 1.8 g/cm<sup>3</sup>, are also possible. There are also sponge-like  
15 parts, on average having low bulk density, with values of 0.1 to 1.0 g/cm<sup>3</sup>. All of those bodies with different shapes and different bulk densities have an open pore system. They are referred to hereinbelow as a "primary product".

20 Material composites formed of such a primary product and synthetic resins or plastics materials perform a variety of tasks. Synthetic resins or plastics materials lower the permeability, improve the surface properties, for example the scratch resistance, increase the strength to a small extent,  
25 lower the thermal stability of a material composite containing expanded graphite, and can also reduce the electrical

conductivity or modify the resistance to media. An expedient technique for the production of such material composites is impregnation.

- 5 According to German Patent DE 32 44 595 C2, corresponding to UK Patent Application GB 2 131 500 A, the sticking action of graphite foils to metal surfaces can be reduced by impregnating the primary product with furan resin in regions close to the surface.

10 According to the prior art, the substantial impregnation of shaped bodies made of expanded and partially recompressed graphite is difficult. In order to overcome the difficulties, International Publication No. WO 99/16141, corresponding to  
15 U.S. Patent No. 6,037,074, teaches that such a body can be satisfactorily impregnated when mineral fibers are interspersed therein. Those fibers also pass through the surface of the particular bodies. In that way, small channels are formed along those mineral fibers, in which the resin can  
20 flow into the interior of the bodies during the impregnation. In that specification, a phenolic resin dissolved in acetone, i.e. a solvent-containing thermosetting resin with condensation reactions during the curing, is named as the impregnating agent.

25

Another method for achieving good impregnation of bodies made of expanded graphite resides in converting the desired resins through the use of solvents into low-viscosity liquids, whereby the impregnation becomes more complete. In Published  
5 Japanese Patent Application JP 11 00 040 A2, the thermosetting resins named are based on phenols, epoxides, polyimides, melamines, polyesters and furans, which are used in a mixture solution with polyvinylbutyral.

10 Published Japanese Patent Application JP 1 308 872 A2 describes the solution to other problems. A material composite formed of a glass fiber nonwoven fabric and an expanded graphite foil is produced in order to thus strengthen the latter and overall obtain a liquid-tight material. That  
15 is achieved by impregnating with epoxy resin. The resin penetrates the nonwoven fabric, with the composite material being formed during the subsequent curing of the support part. At the same time, the resin also penetrates into the surface, i.e. partially into the foil, and seals the latter.

20 The impregnation of expanded graphite foil with phenolic resin or epoxy resin, which is set out in Published Japanese Patent Application JP 60 24 2041 A2, corresponding to German Patent DE 35 12 867 C2, serves similar purposes, namely to improve  
25 strength and gas-tightness. The special feature in that case lies in a degassing process for the liquid resins and the foil

present therein which is repeated a number of times,  
presumably with the aim of improving the quality of the  
impregnation.

5 German Published, Non-Prosecuted Patent Application DE 43 32  
346 A1 describes the impregnation of the expanded graphite  
foils for the purpose of improving adhesion to elastomer  
layers lying thereon. The viscosity of the epoxy resins used  
in that case is 2100 to 2400 mPa·s.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10240  
10245  
10250  
10255  
10260  
1026

produce high-quality, synthetic resin-containing graphite bodies from recompressed, expanded graphite is easy to see. All of the processes described have disadvantages, some of which are serious: if resins diluted by solvents and thus having lower viscosity are used during the impregnation, it is true that the impregnation is easier. However, the vapors from the, in most cases, readily volatile solvents cause serious problems during the impregnation itself, especially during subsequent process steps. In particular, as a result of the fact that they escape during the curing of the resins, they leave behind fine channels which raise the permeability of the bodies being produced. If an increased permeability can be neither tolerated nor is desired, a general problem exists. Furthermore, if the curing is not performed very slowly, i.e. is time-consuming, blisters and cracks are formed in the bodies, which lower their quality considerably.

The same applies to resin systems which release gases from condensation reactions during the curing. As a result of the fact that solvents or other gases and vapors escape, a residual porosity arises in the bodies. Attempts are now frequently made to eliminate the residual porosity by one or more additional impregnating operations. The attendant increase in expenditure is clear and the success is really limited. Additionally, solvent-containing resins above all always require measures to allow their safe handling and the

harmless removal or recovery of the solvents, which increases the expenditure even further. However, the solution through the addition of fibers penetrating the surfaces of the body may improve the impregnating properties of the body but does not eliminate the problems outlined for the use of solvent-containing resins releasing vapors or gases. In addition, one always has a product containing certain fibers, which is more expensive to produce.

#### Summary of the Invention:

It is accordingly an object of the invention to provide bodies formed of expanded or at least partially recompressed expanded graphite having a liquid-accessible pore system which is completely or partially filled with an uncured or partially or completely cured synthetic resin, a process for producing the bodies and sealing elements, fuel cell components and heat-conducting elements formed of the bodies, which overcome the hereinafore-mentioned disadvantages of the heretofore-known products and processes of this general type and in which the bodies do not contain any defects such as blisters or cracks that may be caused by reactions of the synthetic resin during the curing, in which the bodies are producible with comparatively little expenditure and in which the bodies are corrosion-resistant, electrically and thermally conductive and are from liquid-permeable to gas-tight, depending on the degree of compression.



With the foregoing and other objects in view there is provided, in accordance with the invention, a synthetic resin-impregnated body, comprising expanded or at least partially recompressed expanded graphite. The graphite contains or is  
5 impregnated with solvent-free, low-viscosity, storage-stable resin systems from the group of isocyanates with their co-reactants and/or epoxy resins or polymers obtained by curing the resin systems.

10 Therefore, the object of the invention is achieved with a body of the type mentioned at the outset, that is the primary product or the body obtained from the impregnated primary product, by at least partial compression containing either  
15 solvent-free and low-viscosity resin systems from the group of isocyanates and their co-reactants, which react to form isocyanurates, urethanes or polyurethanes, and/or of epoxides or cured resin systems produced from the aforementioned group. The resin systems enter into the body by impregnating the  
20 primary product with solvent-free, low-viscosity, storage-stable resin systems from the group of isocyanates and their co-reactants and/or of epoxides.

In order to eliminate the aforementioned disadvantages of  
25 solvent-containing resin systems and nevertheless achieve the advantages of resin systems having low viscosity, the

following special solvent-free resin systems are employed according to the invention presented herein:

1. Epoxy resin systems 1: These epoxy resin systems are characterized by the main components bisphenol-A-diglycidyl ether and methylhexahydrophthalic anhydride. According to the manufacturer's information, the former component constitutes more than 50% by weight and the latter component between 25 and 50% by weight of the total mixture. The mixtures contain a latent catalyst which has a crucial influence on the times when curing at elevated temperatures. Where possible, the resin system does not contain any catalyst. These resin systems have typically, at room temperature, a viscosity of  $500 \pm 100$  mPa·s, and at a slightly elevated processing temperature of 50°C, typically a viscosity of about  $70 \pm 15$  mPa·s.

2. Epoxy resin systems 2: These epoxy resin systems are characterized by the main components bisphenol-F-diglycidyl ether and methylhexahydrophthalic anhydride. According to the manufacturer's information, the former component constitutes more than 50% by weight and the latter component between 25 and 50% by weight of the total mixture. The mixtures additionally contain a latent catalyst which has a crucial influence on the times when curing at elevated temperatures. Where possible, the resin system does not contain any

catalyst. These resins systems have typically, at room temperature, a viscosity of about  $200 \pm 40$  mPa·s, and at a slightly elevated processing temperature of  $50^{\circ}\text{C}$  typically a viscosity of about  $40 \pm 10$  mPa·s.

5

3. Isocyanate resin systems: These resin systems are characterized by the main components diphenylmethane diisocyanate and bis(4,4'-glycidyoxyphenyl)propane.

According to the manufacturer's information, the former component constitutes 75 to 85% by weight and the latter component between 15 and 25% by weight of this partial mixture. Such resin systems are referred to as modified isocyanurate resin systems. One hundred parts of this partial mixture are mixed with five to ten parts of a modified diphenylmethane diisocyanate, which acts as a latent catalyst. The partial mixtures of diphenylmethane diisocyanate and bis(4,4'-glycidyoxyphenyl)propane have, at room temperature, a viscosity of  $40 \pm 10$  mPa·s, and the modified diphenylmethane diisocyanate has a viscosity of  $20 \pm 5$  mPa·s. The stated total mixtures of one hundred parts of the partial mixture and five to ten parts of the modified diphenylmethane diisocyanate have viscosities in the range of from 25 to 40 mPa·s.

The low viscosities, which are essential to the invention, at the processing temperature of the impregnating resins from the three resin systems, ensure good and efficient impregnation of

the primary product. The polyadditions which take place during the curing do not give rise to any low-molecular-weight cleavage products, which could cause blistering or even cracks in the body. The testing of the resin systems is described in more detail in the examples.

On one hand, the (latent) catalysts bring about rapid curing reactions at high temperatures and, on the other hand, they bring about small changes in the chemical process of the resin systems at low temperatures, for instance room temperature, which are employed during the impregnation. These small changes can be proved with the aid of viscosity measurements.

Since the viscosities of the above-stated epoxy resin systems at room temperature are several hundred mPa·s, but the impregnating action is particularly advantageous at viscosities of below one hundred mPa·s, the impregnation with these resin systems is preferably carried out at slightly elevated temperatures in the range of from 40 to 60°C. These slightly elevated temperatures first of all bring about a drastic reduction of the viscosity, but then, in time, a slightly more rapid rise of the viscosity occurs than at room temperature. However, this does not have an adverse effect on the processing behavior of the resin systems. This is shown by the viscosities, which are given below by way of example, of the epoxy resin systems 2 with the component bisphenol-F-

diglycidyl ether. Throughout the investigation period, the resin system is maintained at 50°C:

a fresh resin mixture has approximately 35 mPa·s, after 6 days it has approximately 60 mPa·s and after 12 days it has approximately 150 mPa·s.

The resin system including isocyanate and the co-reactants, which react in time to form isocyanurates, urethanes or polyurethanes, is maintained at room temperature throughout the investigation period and then shows the following viscosities in mPa·s:

a fresh mixture has approximately 35, after three days it has approximately 45, after 10 days it has approximately 50 and after fourteen days it has approximately 60.

The small rate of the changes of the viscosity of the resin systems at low temperatures, for instance room temperature for isocyanates and their co-reactants and 50°C for epoxy resin systems, and over a period of almost two weeks, which is demonstrated by the viscosity measurements, will be referred to hereinafter by the term "high storage stability".

It has been found that the storage stability of the resin systems is not changed by the impregnating operation itself

and by the fact that the resin systems are present in the primary product after the impregnation. This has been shown indirectly, for example, by comparing curing times of pure resin systems and impregnated primary products. In both cases, the same curing times were measured and no differences were found in the quality of the cured resins.

Once the resin has been introduced into the primary product, it tends not to run out of the primary product again. Besides wetting behavior, the following considerations, in particular, are important:

1. During the impregnation, special techniques, such as vacuum or vacuum-pressure impregnation, for example, are employed.

The filling of part of the existing pores is only made possible with the aid of such techniques. For example, filling resistances, such as the flow through narrow pore necks, are overcome in this way. Once the resin has been introduced in this way it cannot escape from the primary product again, without employing any special measures.

2. As explained above, the viscosity of the resins once introduced rises gradually. This rise is small at low temperatures (storage stability), but becomes very pronounced at higher temperatures, causing resins to gel. It is

virtually impossible for such partially gelled resins to escape from the impregnated body.

The expanded graphite used to produce the primary product is formed of fanned-out, wormlike structures in which very fine graphite platelets are joined together in the form of a defective accordion bellows. During the compression of the primary product, these platelets slide in and over one another. They become interlocked and thus come into contact again so as to no longer be able to be released without destruction. This gives rise in the primary product to a porous graphite framework or network which has good electrical as well as good thermal conductivity due to the good contacts between the graphite platelets. Since these properties are based on the framework function of the graphite in the primary product, they are not adversely affected by the impregnation with synthetic resin. They can even be further improved during a subsequent compression of the primary product impregnated with resin.

The primary product is permeated throughout by open pores which are interconnected in a variety of ways. As a result of this network of interconnected pores, the synthetic resin penetrates into the primary-product body during the impregnation and may even completely fill it under suitable conditions. The network of pores then becomes a network of

synthetic resin. Both networks, the graphite network and the pore/synthetic resin network, in combination result in the outstanding properties of the end products thus produced. It is also possible to control the level of properties of the end products by adjusting them in a specific manner. For example, on one hand, a primary-product body which has undergone little precompression and is thus highly porous has a lower electrical and thermal conductivity and a lower degree of anisotropy than a more highly compressed primary-product body. On the other hand, it can take up more synthetic resin and has modified strength properties. This situation is reversed with greatly compressed primary-product bodies. After the impregnation and curing of the synthetic resin, they yield products with improved electrical and thermal conductivity, as well as good mechanical strengths. All of the bodies according to the invention which are described herein are highly impermeable to liquids and gases when their pore network has been completely filled with synthetic resin.

The product described in International Publication No. WO 98/09926 differs from that presented herein in that, in the former, a graphite foil is provided merely with a coating of plastics material for the purpose of reinforcement. The plastics material covers the surface and partially penetrates into the foil.



All of the known methods such as, for example, those described in Published Japanese Patent Application JP 60 24 2041 A2, corresponding to German Patent DE 35 12 867 C2, can be used for the impregnation of the primary-product bodies. It is preferable, however, to use immersion methods, in particular immersion methods with prior evacuation of the vessel containing the primary-product body and flooding of the evacuated vessel with the synthetic resin. Where appropriate, the vessel is also subjected to a gas pressure after it has been flooded with the synthetic resin. If the primary-product body is to be merely impregnated close to the surface or is to be partially impregnated, the impregnating period is shortened or the surfaces from which the impregnation is to start are suitably coated or sprayed with synthetic resin or the body is only partially immersed. Following that treatment, the excess resin is removed from the surface.

An essential aspect of the present invention is efficient, damage-free impregnation and curing. The rapid blister-free and crack-free curing made possible by virtue of the polyaddition reactions has been discussed above. Efficient impregnation depends essentially on the viscosity of the resin systems. This is shown by the following comparison for the vacuum impregnation at 50°C of a primary product of the same type having the following features: flexible graphite foil with a bulk density of 1.0 g/cm<sup>3</sup> and a thickness of 1.0 mm:

Resin system	Viscosity (mPa·s)	Impregnating period (h)	Resin uptake (% by weight)
Epoxy resin systems 2	40	5	15
Epoxy resin systems 1	70	5	8

It is thus possible to introduce about twice the amount of resin into the primary product with the low-viscosity epoxy resin systems 2 than with the higher-viscosity resin systems 1, for otherwise identical boundary conditions and within the same period. If the intention is to introduce merely the smaller amount of resin indicated in the table, this is achieved in an impregnation with the low-viscosity epoxy resin systems 2 in only half the impregnating time as compared with the epoxy resin systems 1. A rapid impregnating operation is of great importance for efficient and cost-effective manufacture.

The primary product can take up an amount of up to 100% of its own weight of resin, depending on the degree of compression of the primary product and the open pore volume which is conditional thereon. If, however, a high electrical conductivity is desired of the end product, it is expedient to start with a primary-product body which has undergone greater precompression and has a lower open pore volume and can then, for example, take up only 20% by weight of resin based on its

own weight. After the curing of the resin, such a body can be highly impermeable to liquids and gases, as seen in the examples, and has good strength properties.

5 Particularly epoxy resins, as well as isocyanate resins with their co-reactants, are known for the fact that their curing reactions start gradually and can also be slowed down again with suitable temperature control. In the case of epoxy and isocyanate resins it is thus possible to preserve a partially  
10 reacted, gel-like state, which is also called a "B state" in technical terminology.

In the B state the synthetic resins have a higher viscosity, but can still be shaped. This B state is advantageously used  
15 within the framework of the present invention. Thus, for example, resins or primary-product bodies or parts impregnated with the resins can be stored over a prolonged period of time or transported during this time. Further steps for the intermediate treatment of the impregnated bodies are possible.

20 For example, such bodies can be machined, e.g. cut, or a number of them can be laminated together to form a stack. However, the fact that the primary-product bodies containing a resin in the B state can be brought into their final shape in suitable shaping configurations and molds is of particular  
25 importance for the invention. During the accompanying pressure treatment, the gel-like resins are, in practice, no

longer squeezed out of the pore system of the body as is the case in an uncontrollable manner with resins which cannot be converted into a gel state. After the shaping, the resin part of the resin-impregnated primary-product body is cured. This is carried out, for example, in a curing chamber at the prescribed temperatures and times.

If the shaping configurations are equipped with apparatus for curing the resins, the shaping operation can even be combined with the curing of the resin in the body. The desired end product is thus obtained directly in an advantageous manner. Such a procedure is interesting particularly when relatively large series of components or bodies are to be produced by using the techniques described above and a number of process steps are to be efficiently combined in the manner outlined. It is convenient for the impregnated primary product, which is generally in the form of a semifinished product or blank, to be put into a mold which is already hot and for the mold to be closed for this purpose. The semifinished product thereby takes on the desired geometry, is simultaneously thoroughly heated and cures completely.

The curing takes place at 120 to 180°C with latently catalyzed resin systems from the group of isocyanates and their co-reactants or/and from the group of the epoxides. A curing time of two hours is sufficient with such systems if the

temperatures lie at the lower end of the specified temperature range. If a relatively high temperature at the upper end of the specified temperature range is chosen, a curing time of fifteen minutes is sufficient.

5

When resin systems from the group of isocyanates and their co-reactants or/and from the group of epoxides are not latently catalyzed, curing is effected in the same temperature range of 120 to 180°C, but curing times of twenty-four to forty hours are then necessary. If a relatively high temperature at the upper end of the specified temperature range is chosen, a curing time of twenty-four hours is sufficient. If the temperatures lie at the lower end of the specified temperature range, curing for up to forty hours is required.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500

A relatively wide variety of graphites based on synthetic production and natural occurrence exists, both types being mentioned in U.S. Patent No. 3,404,061. Only natural graphite will be discussed hereinbelow, with the graphite being present as raw material in the bodies described herein.

20

Natural graphite is obtained by mining and is separated from the gangue rock with considerable effort. Nevertheless, very small amounts of rock also remain, attached to the natural graphite flakes or having intergrown into the flakes. Those "foreign constituents" are characteristic of every source of

25

natural graphite and can also be specified as an ash value. A method for determining such ash values is described in DIN (German Industrial Standard) 51 903 under the title "Testing of Carbon Materials - Determination of the Ash Value".

5

In view of the end uses of the synthetic resin-containing graphite bodies according to the invention, the ash values and ash composition of the graphite that is present are quite important.

10

If such bodies are employed, for example as inherently corrosion-resistant seals in installations subjected to corrosive media, certain ash constituents together with the corrosive medium may result in pitting in the corrosion-resistant seals adjoining flanges or bushes of stuffing-box packings and eventually lead to the failure thereof.

15

Another example of a possible adverse effect of too high an ash value or an unfavorable ash composition of the graphite in a synthetic resin-containing body according to the invention is found in fuel cell technology. Thus, for example, bipolar plates of proton exchange membrane fuel cells can be produced from the material according to the invention. If such a plate now has too high an ash content, some of the harmful ash constituents may be released from the plate during the operation of the fuel cell and poison the sensitive catalysts

20

25

located close to the surfaces of the bipolar plate, resulting in a premature loss of power of the cell.

Due to the potential adverse effects of an excessively high ash content, the ash content of the graphite used to produce the bodies according to the invention is 4 per cent by weight and less, preferably less than 2 per cent by weight and in special cases no more than 0.15 per cent by weight.

10 It may be convenient to strengthen the body according to the invention with fillers, with the selection of the fillers having to be matched to the application (e.g. a fuel cell).

15 Fillers may be electrically conductive materials closely related to expanded natural graphite, such as, for example, materials from the group consisting of naturally occurring flake graphites, synthetically produced electrographites, carbon blacks or carbons, and graphite or carbon fibers.

Furthermore, use may be made of silicon carbide in granular or fibrous form or even electrically non-conductive ceramic or mineral fillers in granular, platelike or fibrous form, such as silicates, carbonates, sulfates, oxides, glasses or selected mixtures thereof.

25 The bodies according to the invention can be used wherever electrically and thermally conductive components of low weight together with good corrosion resistance are required. Further

properties which are essential for various applications are low ash values and relatively high impermeability. The bodies according to the invention are used in particular for components of fuel cells, for seals and for heat-conducting elements, for example for conducting away the excess heat from integrated circuits.

Other features which are considered as characteristic for the invention are set forth in the appended claims.

Although the invention is described herein as embodied in impregnated bodies made of expanded graphite, a process for producing such bodies and sealing elements, fuel cell components and heat-conducting elements formed of the bodies, it is nevertheless not intended to be limited to the details given, since various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of specific embodiments when read in connection with the accompanying examples. In addition, methods for obtaining



data on electrical properties and gas-tightness for the examples are dealt with now.

In order to determine gas-tightness, a resin-impregnated graphite body was pressed as a separating plate (test specimen) between two chambers of a testing apparatus. A constantly maintained helium gas pressure of 2 bar absolute prevailed in a first chamber. A metal grid which mechanically supported the test specimen was disposed in a second chamber.

In addition, this chamber was connected at ambient pressure to a liquid-filled burette, such as that which is used, for example, in the leakage measurement of flat seals according to DIN 3535.

The helium gas emerging from the first chamber and diffusing through the test specimen was collected in the second chamber and measured by displacement of the liquid in the burette. It was thus possible to determine the volume of the helium gas which diffused through the sample per unit of time. While taking the helium density and the testing area into account, a leakage rate was ascertained which is specified by a unit  $\text{mg}/(\text{m}^2 \cdot \text{s})$ .

The material composite of partially recompressed expanded graphite and synthetic resin has anisotropic properties, i.e. the individual graphite platelets of the expanded graphite

have a preferred orientation due to the production technique. For example, the electrical resistance parallel to this preferred orientation is low and perpendicularly thereto it is higher. In the present case, the cured shaped bodies according to the invention were characterized comparatively by measuring the electrical resistance perpendicularly to the preferred orientation of the graphite layers. For this purpose, the body was clamped between two gold-plated electrodes with a diameter of 50 mm, with defined and in each case identical surface pressure. The electrical resistances R established with the aid of a device (Resistomat 2318) from the firm Burster (Gernsbach, Germany) are specified by a magnitude [ $\text{m}\Omega$ ] hereinbelow.

#### Example 1

Plates made of partially recompressed expanded graphite (primary-product plates) with an ash value of less than 2% by weight, a thickness of 1 mm and a bulk density of  $1.0 \text{ g/cm}^3$  are subjected to a vacuum impregnation treatment with latently catalyzed epoxy resin systems. Epoxy resin systems 1 and 2 were used, and came from the firm Bakelite (Duisburg, Germany). Epoxy resin systems 1 bear the trade name Rütapox VE 4834 and had a viscosity of approximately  $70 \text{ mPa}\cdot\text{s}$  at  $50^\circ\text{C}$ . Epoxy resin systems 2 bear the trade name Rütapox M4-1158-CK and had a viscosity of approximately  $40 \text{ mPa}\cdot\text{s}$  at  $50^\circ\text{C}$ .

The primary-product plates were introduced into an evacuable receptacle and heated to 50°C. After application of a vacuum (approximately 10 mbar residual pressure), the resin system which had been previously heated to 50°C was sucked into the  
5 receptacle, so that the primary-product plates were completely surrounded by resin. After the impregnating period indicated in Table 1, the now impregnated plates were taken out of the bath and, after the resin adhering to the surface had been wiped off, were weighed. The impregnated plates were  
10 subsequently cured at 150°C in a preheated circulating-air oven for 30 minutes. Despite this shock curing, the plates showed no blisters or cracks at all. The values determined for the impregnating experiments with the epoxy resin systems 1 and 2 and comparative values for a non-impregnated primary-  
15 product plate of the same type are summarized in Table 1. The resin system used, the impregnating period, the resin content of the impregnated body determined after the curing, its electrical volume resistance  $R$ , measured perpendicularly to the preferred orientation of the graphite platelets, and the  
20 helium permeability  $\lambda$  measured perpendicularly to the preferred orientation of the graphite platelets, are shown.

	Impreg- nating period[h]	Viscosity [mPa·s]	Resin content [%]	R [mΩ]	$\lambda$ [mg/ (m <sup>2</sup> ·s)]
Epoxy resin systems 1	10	70	15	0.52	0.07
Epoxy resin systems 2	5	40	14.6	0.39	0.04
Non- impreg- nated primary product plate	-	-	0	0.28	0.32

Table 1:

Comparison of the volume resistance R and the helium permeability  $\lambda$  of an epoxy resin-impregnated primary product (thickness 1 mm, bulk density 1.0 g/cm<sup>3</sup>) with a non-impregnated primary product (thickness 1 mm, bulk density 1.0 g/cm<sup>3</sup>).

As can be seen in Table 1, virtually the same resin content of approximately 15% is achieved after only 5 hours with the low-viscosity epoxy resin systems 2 based on bisphenol-F-diglycidyl ether as with the higher-viscosity epoxy resin systems 1 based on bisphenol-A-diglycidyl ether after an impregnating period of ten hours.

A comparison of the material composite and the non-impregnated primary product shows the following: as a result of the resin

impregnation, the helium permeability of the bodies is reduced by a factor of five and eight, respectively. The volume resistance is only slightly increased by the impregnating treatment.

5

#### Example 2

In this example, the epoxy resin systems 1 were used without a latent catalyst. The primary-product plate employed was of the same type as that employed in Example 1. Similarly, the impregnating conditions were the same as those in Example 1 with regard to the procedure, time and temperature.

The difference, however, is the curing behavior of the resins. In order to cure the impregnated primary-product plate, a curing period of 24 h at 150°C is required in this example.

The epoxy resin systems 1 have a high storage stability at 50°C without a latent catalyst. Starting from 30 to 70 mPa·s, the viscosity rises to from 65 to 90 mPa·s at 50°C after four weeks' storage. Resin systems with a latent catalyst exhibit a rise in viscosity to over 100 mPa·s after only approximately 1 week.

#### Example 3

In this example, the following plates made of partially recompressed expanded graphite (primary-product plates) were

impregnated with an isocyanate resin system by immersion at room temperature.

	Type of primary product plate	Thickness [mm]	Bulk density [g/cm <sup>3</sup> ]
Example 3a	F02510C	0.25	1.0
Example 3b	L10010C	1.0	1.0
Example 3c	L20010C	2.0	1.0
Example 3d	L40005C	4.0	0.5

5 Table 2:

Plates made of partially recompressed expanded graphite (primary-product plates) used for the impregnation with an isocyanate resin system.

10 The isocyanate resin system used had the following composition:

100 parts of Blendur VP KU 3-4520

10 parts of Blendur VP PU 90IK06

15 Both resin components came from the firm Rhein Chemie Rheinau GmbH (Mannheim, Germany). Blendur VP KU 3-4520 is formed of 75 - 85% by weight of diphenylmethane diisocyanate and 15 - 25% by weight of bis(4,4'-glycidyloxyphenyl)propane. Blendur VP PU 90IK06 is the latent catalyst which is formed

predominantly of modified diphenylmethane diisocyanate,  
according to the manufacturer's information.

The various primary-product plates were completely immersed in  
the resin system. After an immersion time of 10 hours, the  
plates were removed from the resin bath and the resin adhering  
to the surface was wiped off. The impregnated plates were  
then put into a preheated circulating-air oven and cured at  
160°C for 30 minutes. After this shock curing, the plates had  
no blisters or cracks at all.

The resin contents of the primary-product plates listed as  
well as selected material properties are shown in Table 3 in  
comparison with non-impregnated primary-product plates.

	Type of primary- product plate	Resin content [%]	R [m $\Omega$ ]	$\lambda$ [mg/ (m <sup>2</sup> ·s)]
Example 3a	F02510C	29.4	0.24	< 0.0015
Example 3b	L10010C	16.0	0.43	0.028
Example 3c	L20010C	11.4	0.57	—
Example 3d	L40005C	38.9	0.85	—
Example 3a'	F02510C	0	< 0.10	1.50
Example 3b'	L10010C	0	0.28	0.32

Table 3:

A comparison of the volume resistance R and the helium permeability  $\lambda$  of cured, impregnated primary product (varying thickness and bulk density) with non-impregnated primary product (of likewise varying thickness and bulk density); Examples 3a and 3a' as well as Examples 3b and 3b' in particular, are to be compared.

As is evident from Table 3, the resin uptake or absorption varies depending on the bulk density of the primary product, with a low bulk density resulting in a high resin uptake or absorption. The impregnated primary product may contain up to 40% resin. The helium permeability of the impregnated plates is lower by more than a factor of ten in comparison with non-impregnated plates. The electrical volume resistance is only moderately increased by the impregnating treatment.

#### Example 4

This exemplary embodiment was concerned with the impregnation of a primary-product plate with the epoxy resin systems without a latent catalyst, and the precuring and shaping thereof after the impregnation with synthetic resin.

The primary-product plate made of partially recompressed expanded graphite had a thickness of 2.7 mm and a bulk density of 0.65 g/cm<sup>3</sup>. The ash value of the graphite was less than or



equal to 0.15% by weight. The vacuum impregnation process was performed at 50°C in accordance with Example 1. After an impregnating period of two hours, the now impregnated plate was taken out of the bath and, after the resin adhering to the surface had been wiped off, weighed. The resin content of the uncured plate was 16%. Subsequently, the plate was put into a circulating-air oven at 150°C for a period of 20 hours and the resin present in the body was converted into the B state. In the B state the resin present was partially gelled and the impregnated plate was still soft and flexible. It was placed in a pressing die preheated to 180°, pressed into the mold for a period of one hour and, as a result, was further compressed. The plate took on the geometry of the pressing mold which was coated with anti-sticking agent. After the pressing mold had been opened, the impregnated and now partially cured shaped body had sufficient stability for it to be removed from the mold without destruction. After a further heat treatment of the shaped body for 12 hours at 150°C, the resin was completely cured. The cured shaped body showed no cracks or blisters at all. Furthermore, none of the resin in the B state was pressed out of the impregnated body by the pressing, so that a continuous resin layer did not accumulate at the surface of the shaped body. As has been shown in practice, excess resin not previously converted into the B state is squeezed out of the body during the pressing in a shaping apparatus. This squeezed-out resin can form a resin skin on

the outer surfaces of the body which has an electrically and thermally insulating action and may be undesirable, depending on the intended use of the product.

#### 5 Example 5

The primary-product plate was of the same type as in Example 4 and had a thickness of 2.7 mm and a bulk density of 0.65 g/cm<sup>3</sup>. This primary-product plate was immersed in an impregnating resin at room temperature for one hour. This resin was formed of 95 parts by weight of Blendur VP KU 3-4520 and 5 parts by weight of Blendur VP PU 90IK06. (Both components were also used in Example 3 with a slightly different composition). After the impregnation, the resin content of the plate was 15% by weight. The impregnated plate was heated at 150°C for a period of nine minutes, in the course of which the resin was converted into the B state and partially gelled. This still-warm plate was subsequently placed in the molding die, which was preheated to 150°C, and was pressed into the mold. The pressing mold coated with anti-sticking agent remained closed for five minutes and was then opened, and the body which was cured in the meantime was removed from the pressing mold.

In this example too, none of the resin in the B state was squeezed out of the impregnated body by the pressing, so that a continuous resin layer did not accumulate at the surface of

the shaped body and the shaped body showed no electrically insulating action at all in the surface region.

Example 6 (comparison, prior art)

- 5 In this example, a solvent-containing epoxy resin system was deliberately used for the impregnation. The following composition was chosen for the resin system:

75 parts of epoxy resin systems 2 (see Example 1) with  
the main components bisphenol-F-diglycidyl ether and  
methylnhexahydrophthalic anhydride without a latent  
catalyst, and  
25 parts of 2-butanone (solvent).

- 15 The viscosity of this solvent-containing resin system was 15 mPa·s at room temperature. The primary product had a bulk density of 1.0 g/cm<sup>3</sup>, a plate thickness of 1 mm and an ash value of less than 2% by weight. The vacuum impregnation was carried out as in Example 1, but at room temperature rather  
20 than at 50°C. After an impregnating period of 6.5 hours, the now impregnated plate was taken out of the bath and, after the resin adhering to the surface had been wiped off, weighed. The resin content was 23% by weight in the uncured state.

- 25 The impregnated plate was then put into a preheated circulating-air oven with a temperature of 150°C and after a

curing period of 30 minutes removed from the oven. The plate was covered in blisters of varying sizes and was completely unusable! Neither a volume resistance nor a helium permeability could be determined thereon.

5

The cured plate covered in blisters showed a marked decrease in weight as compared with the freshly impregnated state. The resin content had dropped as a result of the curing treatment from 23% in the uncured state to 17.8% in the cured state.

10 This was not observed on the samples of Examples 1 to 5, in which solvent-free resin systems had been employed. The loss in weight in Example 6 was attributable to the evaporation of the solvent. The blisters were forced up because the evaporation of the solvent took place not only at the surface of the impregnated body but also in the interior of the body and escape was hindered by the material layers lying above.

15 If a plate impregnated with a solvent-containing resin system were pressed in a molding die and cured, as described in  
20 Example 4 for solvent-free resin systems, the difficulties would only be compounded, because the released solvent vapors would not be able to escape unhindered and consequently defects and blisters would be formed in the body to an increased extent and in an uncontrollable manner. Production  
25 of a shaped body impregnated with a solvent-containing resin by further compression in a pressing apparatus and subsequent

curing is not possible in acceptable production times without a massive reduction in quality of the desired end product.

Comparing Example 6 with Examples 1 to 5 clearly shows the progress which has been achieved with the solution according to the invention.

Besides these above-mentioned examples, a multiplicity of further bodies and procedures can be realized according to the teaching of the present invention. Accordingly, the invention is not restricted to the embodiments illustrated in the examples. Variants which are not shown but which a person skilled in the art could produce due to the information offered by this disclosure are therefore also to be included in this patent application.